




LASER-POWERED SENSOR SYSTEMS




Datasheet

—— LSProbe 1.2 ——

**Electric-Field Probe
(10Hz) 9kHz - 8.2GHz**

The LSProbe 1.2 Field Probe is a high speed, high accuracy and high dynamic range electric-field probe. Its standard frequency range of 9 kHz – 8.2 GHz can be extended to 10 Hz – 8.2 GHz. Best-in-class compensation of linearity, frequency and temperature guarantees accurate measurements from less than 0.1 to at least 1,000 V/m. A dynamic range of 100 dB is achieved for many frequencies, enabling field measurements at more than 10,000 V/m.

Customized high field-strength “X”-variants, supporting up to 30,000 V/m and a damage level of 100,000 V/m, are available upon request. Please contact LUMILOOP support for detailed information.




A single axis, continuously sampling mode, operating at 2 MS/s, can be used for Equivalent Isotropically Radiated Power (EIRP) measurements of IoT products without antenna connectors in accordance with EN 300 328 and EN 301 893.

Laser-powered operation eliminates battery recharging and replacement. Extensive in-house calibration data are provided with each field probe and is handled automatically by the LSProbe Software (TCP Server and GUI). Third-party EMC-software support for R&S EMC32, R&S ELEKTRA, Emcware, BAT-EMC, Tepto, Tile, Win6000, Compliance5/6, ProveEMC, Radimation and RAD-LAB.

LSProbe 1.2 Variants


Variant	Low Band Frequency Ranges		High Band Frequency Range
	10 Hz – 200 MHz	9 kHz – 400 MHz	30 MHz – 8.2 GHz
A ... D	Legacy variants incl. LO, HI, HI+LO with in-house calibration up to 6 GHz.		
E	—	✓	✓
F	✓	—	✓
G	—	✓	15 kV/m ✓
X	✓	✓	✓
Customized for high frequency and electric-field strengths, e.g., 30 kV/m.			




LSProbe 1.2 Field Sensor

Supported Frequency Ranges 9 kHz ... 8.2 GHz 10 Hz ... 8.2 GHz	Variant E, G* F
Detectors Low Band High Band	(10 Hz) 9 kHz ... 400 MHz 30 MHz ... 8.2 GHz
Field Strength Range, Dynamic Range 10 Hz ... 30 MHz (F) 9 kHz ... 30 MHz (E, G) 30 MHz ... 6 GHz (E, F) 6 GHz ... 8.2 GHz (E, F)	<4 V/m ... >7 kV/m, >70 dB <1 V/m ... >10 kV/m, >80 dB <0.1 V/m ... >1 kV/m, >80 dB <1 V/m ... >1 kV/m, >60 dB
Damage Level	>25 kV/m
Sampling Rate, Minimum Pulse Width Burst Mode Continuous Mode Single Axis Continuous Mode	2 MSamples/s, 500 ns 500 kSamples/s, 2 μ s 2 MSamples/s, 500 ns
Analog Rise Time Low Band, low bandwidth Low Band, high bandwidth High Band	1.9 ms 770 ns 330 ns
Resolution	<0.01 dB
Typical Worst-Case Isotropy Error @ 1 GHz @ 3 GHz @ 6 GHz	± 1.0 dB ± 1.7 dB Please see Application Note 8.
Amplitude Accuracy 9 kHz ... 30 MHz 30 MHz ... 1 GHz 1 GHz ... 8.2 GHz	Accredited Cal. at PTB, Germany ± 0.6 dB ± 1.0 dB ± 1.4 dB
Linearity Error	± 0.2 dB relating to 10 V/m
Temperature Stability	± 0.1 dB
Fiber Optic Connectors	FC/ST
Standard Fiber Optic Cables	5 m permanently attached, 15 m FC/ST extension, two E2000 Sacrificial Cable Kits
Max. Fiber Optic Cable Length	1,000 m
Fiber Optic Cable Bending Radius	>30 mm
Ambient Temperature	10 °C ... 40 °C
Dimensions (W x D x H)	46 x 46 x 114 mm ³

*) Variant G, reduced sensitivity to support 15 kV/m



Isotropy @ 1 GHz, normalized E-field rotating around H-vector



Isotropy @ 1 GHz, normalized E-field rotating in E-H-plane

Computer Interface

	CI-250	CI-250 ⁺
PC Interface	USB 2.0	Gigabit Ethernet
Application Software	LUMILOOP TCP Server, LUMILOOP GUI	LUMILOOP TCP Server, LUMILOOP GUI
Trigger Voltage	5 V	5 V
Trigger Connector	BNC	BNC
Laser Wavelength	830 nm	830 nm
Laser, Max. Output Power	1,000 mW	1,000 mW
Laser Class	1M	1M
Laser Shutdown Time	1 ms	1 ms
Fiber Optic Connectors	FC/ST	FC/ST
Number of Fiber Optic Couplers	>6	>6
Input Voltage	5 V ± 5 %	85-305 V, 50/60 Hz
Input Current	<3 A	
Output Voltage		5 V DC (max. 3 A)
Output Current		<3 V
Ambient Temperature	10 °C ... 40 °C	10 °C ... 40 °C
Dimensions (W x D x H)	135 x 120 x 38 mm ³	200 x 88 x 150 mm ³
Certifications	CE, IEC 60825-1:2014	CE, IEC 60825-1:2014

Selected International Standards

ISO	11451-2, WD 11451-5, 11452-2, 11452-11
IEC	61000-4-3, 61000-4-21
EN	300 328, 301 893
Other	RTCA/DO-160



Computer Interface CI-250 Rear Side View



Computer Interface CI-250⁺ Rear Side View

LSProbe Documentation and Application Notes (AN)

- LSProbe User's Manual
- AN 1: Measuring Radio Jammers
- AN 2: Measuring Pulsed Fields
- AN 3: Multi-Probe EUT-Monitoring using EMC32
- AN 4: Reliable Operation of LSProbe Electric-Field Probes
- AN 5: Third Party EMC-Software Integration of LSProbe 1.2 Electric-Field Probes
- AN 6: Calibration of LSProbe Electric-Field Probes
- AN 7: LSProbe 1.2 Variants

LSProbe Accessories

Fiber Connector Cleaning Kit



- optical fiber microscope
- lint-free cassette cleaner wipes
- unfilled isopropyl alcohol (IPA) pipette bottle
- spare FC/ST dust caps and two E2000 locking caps

E2000 Sacrificial Cable Kit



- prevents contamination of connectors
- quick and simple replacement in case of connector burn-in
- includes two 0.5 m E2000 to ST/FC cables
- includes E2000 and ST/FC couplers

Optic Fiber Cable Extension



- fiber optic cable with ST/FC connectors
- includes ST/FC coupler
- arbitrary length of cable available on request

Tabletop Probe Stand Base




- quick positioning for table and ground-plane setups
- horizontal probe position 100 mm relative to all edges
- relative permittivity better than 2.7 @ 1 kHz

Tabletop Probe Stand Mounting Base



- to position the field sensors center at 100 mm, 125 mm, 150 mm, 200 mm or 300 mm above surface
- well-defined field probe alignment with quick mount/release
- relative permittivity better than 2.7 @ 1 kHz

Flexible Probe Stand



- flexible tripod feet for versatile positioning
- vertical position approximately 150 to 250 mm above surface
- strong magnetic feet with rubber coating
- no metal parts
- quick mount/release



LUMILOOP GmbH
Gostritzer Str. 63, 01217 Dresden, Germany
Phone: +49 351 85097870
E-mail: info@lumiloop.de
www.lumiloop.de

Made in Germany



Register your LUMILOOP device and get a free one year warranty extension!
lumiloop.de/support/register